

EUROTRONIC<sup>TM</sup>

### Control & Signal Cable

UL 2464 E196987 

No.Of Core	AWG	mm <sup>2</sup>	Conductor Stranding No./mm	Nominal Overall Diameter mm	Conductor Resistance At 25°C (Ohm/Km)	Standard
4 6 8 10 12	22	0.325	7/0.254	5.6 6.3 6.9 7.3 7.7	54.8	UL2464
4 6 8 10 12 20	20	0.519	21/0.180	6.1 6.9 7.3 8.5 9.4 18.1	34.5	UL 2464
2 4 6 8 10 12	18	0.82	16/0.254	5.7 7.3 8.9 10.5 12.1 13.7	23	UL 2464
1 2 3	16	1.31	26/0.254	5.9 7.9 9.8	14.7	UL 2464

Conductor : Fully annealed tinned copper, stranded

Insulation : Polyethylene grade colour coded, semi rigid PVC

Sheath : PVC

Colour : Grey/Black

Insulation Colour Code : Black, Red, Green, Yellow, White, Blue

Orange/Violet, Brown/Pink

Orange+White, White+Orange

Temperature Range : -10°C to 80°C

Voltage Rating : 300 Volts

Packing : 500m in drum

Comply : UL Standard

